Suction, blower, transport hoses

SSB

Suction, blower, transport hosess

Special clamp for connecting medium and heavy duty hoses, type KUW to connectors on mobile and stationary units

Temperature:	-40°C ... +120°C
Material:	galvanized steel
for protective conduit:	KUW-PVC / KUW-PU-LL / KUW-PU-L / KUW-PU-S / KUW-PU-SE-F

CHARACTERISTICS:

- Properties: rust-protected
- extremely robust
- up to clamping range 214 – 226 mm with a lock, from 230 mm on with two locks

FLEXA No.	DN [mm]	Klemmbereich [mm]	Width/Stärke	PU [pcs.]
10342000050	50,0	50,0-58,0	20-1,0	1
10342000060	60,0	60,0-68,0	20-1,0	1
10342000075	75,0	75,0-83,0	20-1,0	1
10342000080	80,0	80,0-88,0	20-1,0	1
10342000090	90,0	90,0-98,0	20-1,0	1
10342000100	100,0	100,0-108,0	20-1,0	1
10342000120	120,0	120,0-128,0	20-1,0	1
10342000125	125,0	125,0-133,0	20-1,0	1
10342000140	140,0	140,0-148,0	20-1,0	1
10342000150	150,0	150,0-158,0	20-1,0	1
10342000160	160,0	160,0-168,0	20-1,0	1
10342000175	175,0	175,0-183,0	20-1,0	1
10342000180	180,0	180,0-188,0	20-1,0	1
10342000200	200,0	200,0-208,0	20-1,0	1
10342000225	225,0	225,0-233,0	20-1,0	1
10342000250	250,0	250,0-258,0	20-1,0	1
10342000300	300,0	300,0-308,0	20-1,0	1
10342000325	325,0	320,0-328,0	20-1,0	1
10342000350	350,0	350,0-358,0	20-1,0	1

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA´s knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.