

EW 45 M | metric thread

Connectors

Metal connector, elbow 45°, metric outer thread, incl. ferrule and sealing



Temperature: -45°C ... +105°C

Material: nickel-plated brass

IP class [acc. to EN 60529]: IP 67

CHARACTERISTICS:

- Properties: highly watertight and dustproof
- friction-type locking of conduit and connector
- correct grounding
- covering of the conduit ends

APPLICATIONS:

- Application: machine and plant constructions / automotive / shipbuilding / automation / electrical installations / for international applications



FLEXA No.	OD [mm]	Thread type	Conduit ID	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS1 [mm]	WS2 [mm]	Weight [kg/100]	PU [pcs.]
10609000020	3/8 inch	M20 x 1,5	12,5	18,0	10,2	29,0	12,0	58,0	26	22	7,400	10
10609000120	5/16 inch	M20 x 1,5	10,0	14,5	8,3	29,0	13,0	57,0	26	22	7,400	10
10609000025	3/4 inch	M25 x 1,5	21,0	26,5	18,5	38,7	15,0	70,0	35	33	13,600	5
10609000016	3/8 inch	M16 x 1,5	12,5	18,0	10,2	29,0	12,0	57,0	26	22	7,300	10
10609000021	1/2 inch	M20 x 1,5	16,0	21,0	13,9	32,7	13,0	60,0	29	27	10,500	10
10609000032	1 inch	M32 x 1,5	26,5	33,0	23,8	50,0	15,0	84,5	45	42	26,500	5
10609000040	1 1/4 inch	M40 x 1,5	35,5	42,0	31,8	60,0	16,0	98,0	54	51	44,900	2
10609000063	2 inch	M63 x 1,5	51,5	60,0	47,8	85,0	20,0	133,5	77	74	128,000	2
10609000116	5/16 inch	M16 x 1,5	10,0	14,5	8,3	29,0	12,0	57,0	26	22	7,300	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.