

FLEXAhightemp

Protective conduits

Fire protection conduit, non-flammable, calcium-silicate braiding with silicone sheathing

Temperature: -50°C ... +350°C ^
+700°C

Material: calcium-silicate | SI

CHARACTERISTICS:

- Properties: weatherproof
- watertight
- widely resistant to seawater, acids and oils
- good radiation resistance
- abrasive resistant
- very flexible
- non-flammable, even no afterglow
- self-extinguishing DIN 5510 [ST2
- SR2
- S4]



APPLICATIONS:

- Application: steel industry foundries / chemical companies / oil companies / shipbuilders / public transportation / mining industry / glass factories / railway industry



FLEXA No.	Colour	NW [mm]	ID [mm]	OD [mm]	Weight [kg/m]	PU [m]
12061809010	Red	10,0	10,0	17,0	0,119	15
12061809015	Red	15,0	15,0	22,0	0,209	15
12061809020	Red	20,0	20,0	27,0	0,213	15
12061809022	Red	22,0	22,0	29,0	0,239	15
12061809025	Red	25,0	25,0	32,0	0,291	15
12061809030	Red	30,0	30,0	37,0	0,342	15
12061809035	Red	35,0	35,0	42,0	0,390	15
12061809040	Red	40,0	40,0	47,0	0,380	15
12061809050	Red	50,0	50,0	57,0	0,733	15
12061809060	Red	60,0	60,0	67,0	0,750	15

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.