

HG-CU

Protective conduits

Wire braiding consisting of round braided tinned-copper wires with double crossed looping at the different braiding angles, Coverage: >85%

Temperature: -50°C ... +250°C

Material: tinned copper

IP class [acc. to EN 60529]: IP 40

CHARACTERISTICS:

- Properties: axially pushed together, in a certain proportion, depending upon the construction of the braiding up to the double diameter
- easy pulling in of cables
- the braiding becomes tight by stretching
- protection from hot swarfs
- high shielding factor
- screening factor up to 30 MHz acc. to EN 50289-1-6 up to 80 dB



APPLICATIONS:

- Application: cable bundling / machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations / EMC applications



FLEXA No.	Colour	NW [mm]	Aufbau [mm]	Operative range [mm]	Weight [kg/m]	PU [m]
14050701008	Silver	6,0	ID 6, 5,0 - 12,0 mm	5-12,0	0,060	100
14050701013	Silver	10,0	ID 10, 8,0 - 17,0 mm	8-17,0	0,104	50
14050701017	Silver	15,0	ID 15, 12,0 - 22,0 mm	12-22,0	0,098	50
14050701025	Silver	20,0	ID 20, 16,0 - 27,0 mm	16-27,0	0,190	50
14050701040	Silver	25,0	ID 25, 20,0 - 35,0 mm	20-35,0	0,204	25
14050701055	Silver	35,0	ID 35, 25,0 - 45,0 mm	25-45,0	0,240	25
14050701108	Silver	6,0	ID 6, 5,0 - 12,0 mm	5-12,0	0,060	10
14050701113	Silver	10,0	ID 10, 8,0 - 17,0 mm	8-17,0	0,104	10
14050701117	Silver	15,0	ID 15, 12,0 - 22,0 mm	12-22,0	0,098	10
14050701125	Silver	20,0	ID 20, 16,0 - 27,0 mm	16-27,0	0,190	10
14050701140	Silver	25,0	ID 25, 20,0 - 35,0 mm	20-35,0	0,204	10
14050701155	Silver	35,0	ID 35, 25,0 - 45,0 mm	25-45,0	0,240	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.