

RGE

Connectors

Metal conector, safety-type, straight, metric outer thread, incl. special sealing, brass thrust collar and O-ring, for EMC applications


Temperature: -40°C ... +120°C

Material: nickel-plated brass

IP class [acc. to EN 60529]: IP 66

CHARACTERISTICS:

- Properties: highly watertight and dustproof
- friction-type locking of conduit and screw connector
- covered conduit ends
- optimal shielding with high-density



APPLICATIONS:

- Application: machine and plant constructions / automotive / automation / electrical installations / EMC applications



FLEXA No.	OD [mm]	Thread type	Conduit ID	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS1 [mm]	WS2 [mm]	Weight [kg/100]	PU [pcs.]
15126013012	13,0	M12 x 1,5	10,0	14,0	9,0	28,0	10,0	23,0	19	21	2,100	10
15126015016	15,8	M16 x 1,5	12,0	17,0	13,0	29,0	10,0	27,0	23	25	3,300	10
15126021020	21,2	M20 x 1,5	16,0	23,0	16,5	31,0	10,0	31,0	27	29	3,900	10
15126034032	34,5	M32 x 1,5	27,5	36,0	27,5	40,0	13,0	48,0	43	45	11,000	10
15126042040	42,5	M40 x 1,5	35,5	44,0	35,5	40,0	13,0	57,0	52	54	14,900	10
15126054050	54,5	M50 x 1,5	47,0	56,0	44,5	47,0	14,0	70,0	52	66	21,500	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.