

RQGST

Connectors

Plastic connector, quick-type, straight, to connect with metric solid installation tube, high density, incl. conduit clamp


Temperature: -40°C ... +120°C

Material: PA plastics

IP class [acc. to EN 60529]: IP 68 | IP 69K

CHARACTERISTICS:

- Properties: to connect with metric solid installation tube
- incl. conduit clamp
- resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen



APPLICATIONS:

- Application: machine and plant constructions / automation / electrical installations



FLEXA No.	OD [mm]	Colour	Connecting pipe Ø [mm]	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15604015216	15,8	Black	16,0	12,5	23,0	13,0	41,0	21	0,750	50
15604021220	21,2	Black	20,0	17,0	29,5	13,0	45,0	27	1,150	50
15604028225	28,5	Black	25,0	20,5	37,0	15,0	49,5	34	1,700	25
15604034232	34,5	Black	32,0	25,5	44,0	15,0	52,5	40	2,200	25
15604042240	42,5	Black	40,0	32,0	52,0	15,5	54,5	49	3,100	25
15604054250	54,5	Black	50,0	42,5	64,0	16,0	55,5	60	4,000	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.