LKS-M

Connectors

Plastic connector, straight, one-part, metric connecting thread, turnable incl. counternut



Temperature:	-10°C ... +110°C
Material:	plastics [PP]
IP class [acc. to EN 60529]:	IP 61
for protective conduit:	AIRflex-KS

CHARACTERISTICS:

- Properties: rational conduit fitting
- one-part connector body
- conduit screw-out-locking
- covering of the conduit ends
- vibrationproof and tensionproof

FLEXA No.	OD [mm]	Colour	Thread type	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020114016	17,0	Grey	M16 x 1,5	10,0	24,0	15,0	41,0	22	0,785	20
15020114020	21,0	Grey	M20 x 1,5	13,0	30,0	15,0	44,6	27	1,250	20
15020114025	25,0	Grey	M25 x 1,5	17,5	35,0	15,0	44,4	32	1,600	20
15020114032	31,0	Grey	M32 x 1,5	23,5	45,8	15,0	48,6	38	2,500	10
15020114040	38,0	Grey	M40 x 1,5	30,0	55,5	18,0	54,7	46	3,570	10
15020114050	47,0	Grey	M50 x 1,5	38,0	65,8	18,0	57,0	55	5,280	5
15020114063	57,0	Grey	M63 x 1,5	48,0	81,0	19,0	79,5	70	14,860	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA´s knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.