UL-listed products

RQW-N | NPT thread

Protective conduit systems | UL listed

Plastic connector, quick-type, elbow 90°, NPT outer thread, integrated snap-in sleeve with sealing, high density

Température:	-40°C ... +120°C
Matériau:	PA plastics
Protection [acc. to EN 60529]:	IP 68	IP 69K

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen

APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations

FLEXA No.	Couleur	DE [mm]	Filetage NPT	Ø I [mm]	Ø B [mm]	C [mm]	E [mm]	F [mm]	Ø D [mm]	Poids [kg|100]	UE [Pcs]
15020057206	Black	21,2	1/2 inch	16,0	29,5	13,0	51,0	48,5	27,0	1,880	50
15020039221	Black	28,5	3/4 inch	21,0	37,0	14,0	57,5	57,0	34,0	3,040	25
15020039228	Black	34,5	1 inch	28,0	44,0	16,0	67,5	67,5	43,0	4,800	10
15020057207	Black	42,5	1 1/4 inch	35,0	52,0	18,0	83,0	76,0	52,0	6,900	10
15020057208	Black	42,5	1 1/2 inch	36,5	54,0	16,5	83,0	76,0	56,0	7,350	10
15020057209	Black	54,5	1 1/2 inch	41,0	64,0	18,0	95,0	87,0	64,5	11,800	5
15020057210	Black	54,5	2 inch	52,0	66,0	21,0	100,0	90,0	65,0	10,900	5

Les recommandations concernant les domaines d'application, les domaines d'utilisation, les produits ou les combinaisons de produits sont faites par FLEXA au mieux de ses connaissances et de ses expériences antérieures. L'utilisation des produits FLEXA pour des applications spécifiques doit être vérifiée par l'utilisateur. Tous les textes publiés, les images de produits, les dessins de produits et les listes ne peuvent être copiés, modifiés ou changés sans le consentement de FLEXA. Les dessins techniques, les approbations, les certificats et les résultats du propre laboratoire d'essai de FLEXA sont disponibles sur demande. Pour les fautes d'impression, les erreurs dans les dessins techniques, les erreurs et les modifications techniques, nous n'assumons aucune responsabilit.